



SRG

Schulz + Rackow Gastechnik GmbH

SRG LPG High Pressure First Stage Tank Regulator Type 512



Technical Description

Inlet Connections	Outlet Connection	Color
<ul style="list-style-type: none"> ◆ male POL ◆ 1/4" NPT female ◆ G 1/2" female ◆ other threads available 	<ul style="list-style-type: none"> ◆ G 1/2" female ◆ other threads available 	<ul style="list-style-type: none"> ◆ blue ◆ other colors available on request

The equipment features

- OPSO with visual indicator
- Pressure test points
- Reset tool for OPSO
- PRV outside
- Insect filters on vents
- Bodies and bonnets made of die casting aluminium

Technical data

- Pressure limit = PN 25
- Capacity = 24 kg/hr.
- Inlet connections = male 0,880 POL (CGA 510) with stainless steel nipple
- Outlet connections = G 1/2" female
- Inlet pressure range = 1,5 – 16 bar
- Outlet pressure setting range = 0,5-2,0 bar
- Set pressure OPSO = specified by customer in accordance with international standards
- Set pressure PRV = specified by customer in accordance with international standards

Optional extras

- Alternative outlet pressure, OPSO and PRV settings
- Alternative inlet and outlet connections
- Outlet connections with solder fittings or compression fittings
- Range of installation fittings for above and below ground tanks
- Emergency supply connection
- Pressure gauge
- Outlet 3 o'clock position

Quality standards

The regulators are manufactured in Germany. SRG's quality-control system carries an **ISO 9001** certificate and is continually assessed by the Notified Body.

512 / 1353-001