



SRG

Schulz + Rackow Gastechnik GmbH

SRG LPG Adjustable High Pressure Tank Regulator Type 517



Technical Description

Inlet Connections	Outlet Connection	Color
<ul style="list-style-type: none"> ◆ POL male ◆ ¼" NPT female ◆ G ½" female ◆ other threads available 	<ul style="list-style-type: none"> ◆ G ½" female ◆ other threads available 	<ul style="list-style-type: none"> ◆ blue ◆ other colors available on request
The equipment features		
<ul style="list-style-type: none"> • OPSO with visual indicator • Pressure test points • Reset tool for OPSO • Pressure gauge • PRV outside • Insect filters on vents • Bodies and bonnets made of die casting aluminium 		
Technical data		
<ul style="list-style-type: none"> • Pressure limit = PN 25 • Capacity = 24 kg/hr. / 40 kg/hr. / 50 kg/hr. / 65 kg/hr. (different types available) • Inlet connections = male 0,880 POL (CGA 510) with stainless steel nipple • Outlet connections = G ½" female • Inlet pressure range = 1,6 – 16 bar • Outlet pressure setting range = 0,7 – 5,0 bar (adjustable) • Set pressure OPSO = specified by customer in accordance with international standards • Set pressure PRV = specified by customer in accordance with international standards 		
Optional extras		
<ul style="list-style-type: none"> • Alternative outlet pressure, OPSO and PRV settings • Alternative inlet and outlet connections • Outlet connections with solder fittings or compression fittings • Range of installation fittings for above and below ground tanks • Emergency supply connection • Outlet 3 o'clock position 		
Quality standards		
<p>The regulators are manufactured in Germany. SRG's quality-control system carries an ISO 9001 certificate and is continually assessed by the Notified Body.</p>		

517 / 1353-001



SRG Schulz + Rackow Gastechnik GmbH · P.O. Box 1260 · D-35068 Gladenbach
 Tel.: +49-(0)6462-9392-0 · Fax: +49-(0)6462-9392-91 · e-mail: zentrale@srg-technik.de